



128500 VI - Masking Tape

Description	Masking tape with a Washi (Japanese flat paper) backing and a acrylic clear adhesive.
Product properties	<ul style="list-style-type: none">* Application time: at least after 40 minutes from previous paint application in indoor temperature conditions.* Especially suited for a variety of indoor paint works* Easy indoor removability up to 15 days after application* 1 week UV resistance.* It is suggested not to apply the tape with temperatures lower than 10#C
Applications	This tape is able to ensure high performances when blade-sharp painting works are required. It is mostly suitable for delicate surfaces where low tack and adhesion performances are required, like on wallpaper, last touches & adjustments and restoration works.
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	Paper	
Adhesive	Acrylic	
Colour	Violet	
Thickness Total	0,075 mm	2,95 Mils
Adhesion on stainless steel	2,25 N/25mm	0,514 Lbs/inch
Tensile strength length	62,5 N/25mm	14,3 Lbs/inch
Elongation length	3 %	

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Benelux B.V.
Van Hennaertweg 10
2952 CA Alblasterdam
tel +31 (0)78 699 21 00
fax +31 (0)78 699 21 99
www.stokvistapes.nl
info@stokvistapes.nl